

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 November 2001 (01.11.2001)

PCT

(10) International Publication Number
WO 01/81809 A1

(51) International Patent Classification⁷: **F16L 11/16**

(21) International Application Number: **PCT/DK01/00262**

(22) International Filing Date: **11 April 2001 (11.04.2001)**

(25) Filing Language: **Danish**

(26) Publication Language: **English**

(30) Priority Data:
PA 2000 00672 25 April 2000 (25.04.2000) DK
PA 2000 01707 15 November 2000 (15.11.2000) DK

(71) Applicant (for all designated States except US): **NKT FLEXIBLES I/S [DK/DK]**; Priorparken 510, DK-2605 Brøndby (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GLEJBØL, Kristian [DK/DK]**; Kvædehaven 109, DK-2600 Glostrup (DK). **WEDEL-HEINEN, Jakob [DK/DK]**; Mosehøjvej 46B, DK-2920 Charlottenlund (DK). **RYTTER, Jan, Christian [DK/DK]**; Kastrupvej 18, 4. tv., DK-2300 København S (DK).

(74) Agent: **LARSEN & BIRKEHOLM A/S**; Skandinavisk Patentbureau, Banegårdspladsen 1, P.O. Box 362, DK-1570 København V (DK).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, FR, GB, GR, GU, HK, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **ARMOURED, FLEXIBLE PIPE AND USE OF SAME**



(57) Abstract: A flexible armoured pipe, which comprises an inner liner, which is surrounded by a pressure armour, is built up by the joining together of profiles, which have a number of recesses. According to the invention, the profiles are configured as K-profiles (10, 16, 17), which have recesses (10a, 10b, 10c, 10d), which are arranged in adjoining surfaces of the profile. When the profiles are brought together, the recesses form a cavity in which a locking element (12, 14, 18) can be

inserted, the function of which is to prevent displacement of the K-profiles at right-angles to the axial direction of the pipe when this is exposed to axial, compressive forces. The locking element can be I-shaped (14), be circular or be configured as a wire (18) with a C-shaped cross-section. The locking element can also be made either of a rigid or an elastic, deformable material. With a C-shaped locking element, the whole of the cavity, which is formed by the recesses, is not filled out. A channel is hereby formed through which undesired fluids can be led away or through which cleaning fluids can be introduced.

WO 01/81809 A1